



VIVAX
METROTECH

Remote Antenna

Technical Specifications V2.5



Worldwide Locations

World Headquarters, United States of America

Vivax-Metrotech Corporation

3251 Olcott Street, Santa Clara, CA 95054, USA

T/Free : 1-800-446-3392

Tel : +1-408-734-3880

Fax : +1-408-734-1415

Website : www.vivax-metrotech.com

Email : SalesUSA@vxmt.com

Central/South America and the Caribbean

Ventas para América Latina

3251 Olcott Street, Santa Clara, CA 95054, USA

T/Free : 1-800-446-3392

Tel : +1-408-734-3880

Fax : +1-408-743-5597

Website : www.vivax-metrotech.com

Email : LatinSales@vxmt.com

Canada

Vivax Canada, Inc.

41 Courtland Ave Unit 8, Vaughan, ON L4K 3T3, Canada

Tel : +1-289-846-3010

Fax : +1-905-752-0214

Website : www.vivax-metrotech.ca

Email : SalesCA@vxmt.com

United Kingdom

Vivax-Metrotech Ltd.

Unit 1, B/C Polden Business Centre, Bristol Road, Bridgwater, Somerset, TA6 4AW, UK

Tel : +44(0)1793 822679

Website : www.vivax-metrotech.co.uk

Email : SalesUK@vxmt.com

France

Vivax-Metrotech SAS

Technoparc - 1 allée du Moulin Berger, 69130 Ecully, France

Tel : +33(0)4 72 53 03 03

Fax : +33(0)4 72 53 03 13

Website : www.vivax-metrotech.fr

Email : SalesFR@vxmt.com

Germany

Metrotech Vertriebs GmbH

Am steinernen Kreuz 10a
96110 Schesslitz

Tel : +49 9542 77227-43

Website : www.vivax-metrotech.de

Email : SalesEU@vxmt.com

China

Vivax-Metrotech (Shanghai) Ltd.

Building 10, Lane 1158 Zhongxin Rd.,
Songjiang District, Shanghai, China, 201615

Tel : +86-21-5109-9980

Website : www.vivax-metrotech.com

Email : SalesCN@vxmt.com.cn

A. Typical Applications

Item	Parameter
Description	Single-channel stethoscope
Uses	This will aid in cable identification, particularly in situations where multiple cables are bundled together or in the same cable tray.

B. Characteristics

Item	Parameter
Construction	POM (Polyoxymethylene)
Weight	0.3lbs (0.125kg)
Dimension	1.5-inch (Dia.) x 2.2-inch (L) (39mm x 55mm)
Cable Length	53-inches (1.3m)
Environmental	IP54
Manufacturing	ISO 9001:2015
External Connectors	<ul style="list-style-type: none"> - 1 x 8-pin pull-release plug - ¼ -Inch/ 6.35mm female threads
Temperature Range	Operating: -4°F to 122°F (-20°C to 50°C) Storage : -40°F to 140°F (-40°C to 60°C)
What's in the Box	Remote Antenna Quick Guide
Compatible Accessory Options	Clamp extension rod (with ¼"/6.35mm stud)

C. Operational

Item	Parameter
Frequency Range	512Hz to 200kHz, SD, and SiS
Compatible Receivers	vLoc3 Series Receivers. SD mode is an option and must be ordered or retrofitted in most vLoc3 receivers. SD mode is not available in the vLoc3-9800 or vLoc3-Cam. SiS mode is only available in the vLoc3-5000 receiver when used with the SiS transmitter.

D. Shipping and Packaging

Item	Parameter
Shipping Weight	0.45lbs (0.203kg)
Shipping Dimensions	9.8-inch(L) x 3.7-inch(W) x 2.4-inch(H) (250mm x 95mm x 62mm)

E. Warranty

Item	Parameter
Warranty	12 months

Disclaimer: Product and accessory specifications and availability information are subject to change without prior notice.