



VIVAX
METROTECH

VM-540

Technical Specifications V1.6



Worldwide Locations

World Headquarters, United States of America

Vivax-Metrotech Corporation

3251 Olcott Street, Santa Clara, CA 95054, USA

T/Free : 1-800-446-3392

Tel : +1-408-734-3880

Fax : +1-408-734-1415

Website : www.vivax-metrotech.com

Email : SalesUSA@vxmt.com

Central/South America and the Caribbean

Ventas para América Latina

3251 Olcott Street, Santa Clara, CA 95054, USA

T/Free : 1-800-446-3392

Tel : +1-408-734-3880

Fax : +1-408-743-5597

Website : www.vivax-metrotech.com

Email : LatinSales@vxmt.com

Canada

Vivax Canada, Inc.

41 Courtland Ave Unit 8, Vaughan, ON L4K 3T3, Canada

Tel : +1-289-846-3010

Fax : +1-905-752-0214

Website : www.vivax-metrotech.ca

Email : SalesCA@vxmt.com

United Kingdom

Vivax-Metrotech Ltd.

Unit 1, B/C Polden Business Centre, Bristol Road, Bridgwater, Somerset, TA6 4AW, UK

Tel : +44(0)1793 822679

Website : www.vivax-metrotech.co.uk

Email : SalesUK@vxmt.com

France

Vivax-Metrotech SAS

Technoparc - 1 allée du Moulin Berger, 69130 Ecully, France

Tel : +33(0)4 72 53 03 03

Fax : +33(0)4 72 53 03 13

Website : www.vivax-metrotech.fr

Email : SalesFR@vxmt.com

Germany

Metrotech Vertriebs GmbH

Am steinernen Kreuz 10a
96110 Schesslitz

Tel : +49 9542 77227-43

Website : www.vivax-metrotech.de

Email : SalesEU@vxmt.com

China

Vivax-Metrotech (Shanghai) Ltd.

Building 10, Lane 1158 Zhongxin Rd.,
Songjiang District, Shanghai, China, 201615

Tel : +86-21-5109-9980

Website : www.vivax-metrotech.com

Email : SalesCN@vxmt.com.cn

A. Description and Typical Applications

Item	Parameter
Model Name	VM-540
Model Number	VX215-05
Description	VM-540 Sonde Locator
Uses	Locating & pinpointing sondes, push camera sondes and crawler camera sondes.

B. Characteristics

Item	Parameter
Construction	<ul style="list-style-type: none"> - Carbon fiber reinforced antenna tube - High-impact thermoplastic (ABS) injection molded housing
Weight	1.37lbs (0.62kg)
Dimensions	37.6in(L) x 3.2in(W) x 2.8in(H) (955mm x 80mm x 70mm)
Display	Dot Matrix, 98 x 64 dots, COG LCD with backlight
Receiver Antennas	2 x Ferrite Antennas
Battery	2 x AA Alkaline batteries
Battery Life	Typically, 20 hours of continuous use at 70°F (21°C)
Environmental	IP54 and NEMA 4
Manufacturing	Designed and manufactured per ISO 9001:2015
External Connectors	Mini-USB socket for programming
Temperature Range	Operating: -4°F to 120°F (-20°C to 50°C) Storage: -40°F to 140°F (-40°C to 60°C)
Compliance and Approvals	<ul style="list-style-type: none"> - Complies with European standard CE (Directive 99/5/EC) <ul style="list-style-type: none"> • EN 55011 • EN 61000-4-2 • EN 61000-4-3 • EN 61000-4-8 - Complies with FCC Rules Part 15 - CFR 47 Part 15: 2006
What's In the Box	<ul style="list-style-type: none"> - VM-540 Receiver - Soft carry bag - Mini-USB Cable - AA Battery holder - Alkaline batteries (depending on the region) - Quick guide

Compatible Accessories Options	Sondes: D18 Sonde – 0.72"/18mm diameter, 512 or 640Hz D23 Sonde – 0.90"/23mm diameter, 512 or 640Hz D38 Sonde – 1.5"/38mm diameter, 33kHz D64 Sonde – 2.4"/64mm diameter, 33kHz
---------------------------------------	--

C. Operational

Item	Parameter
Information Displayed	The Dot Matrix display shows depth, signal level, and battery condition.
Configuration	<ul style="list-style-type: none"> - On/off/speaker button <ul style="list-style-type: none"> • Short press to turn on • Short press toggles volume and volume off • Long press to turn off - Auto shut down - The unit will shut down if no control button is touched for 15 mins. - "+" increases sensitivity - "-" decreases sensitivity - Depth button <ul style="list-style-type: none"> • Short press for depth measurement • Long press for frequency selection
Operating Modes and Frequencies	<ul style="list-style-type: none"> - 512Hz, 640Hz, 33 kHz sonde frequencies - 50Hz or 60Hz passive power mode
Data Logging	N/A
Data Transfer	N/A
Gain / Scaling Control	Fully automatic using - / + keys, one-touch returns to center scale (60% of FSD)
Compatible Transmitters	N/A, sondes only

D. Shipping and Packaging

Item	Parameter
Shipping Weight	4.4lbs (2kg)
Shipping Dimension	47in(L) x 3in(W) x 6.7in(H) (1195mm x 80mm x 170mm)

E. Warranty

Item	Parameter
Warranty	One year

F. Firmware Updates

Item	Parameter
Software	Firmware can be upgraded using a PC with a USB port.

Disclaimer: Product and accessory specification and availability information are subject to change without prior notice.