















# Transmitter Accessories and Signal Clamps

## Direct Connection Leads and Accessories


Picture	Order Code	Description	Plug Type	1-Watt 5-Watt 10-Watt	25-Watt	VM-550FF VM-560FF	VM-810 VM-850 vScan
<b>Direct Connection Lead, Standard Clips</b>							
	2.205.01.00018	Direct Connection Lead with Standard Clips are for day to day use where the size of the targeted lines varies, and connections are to common services.		✓	-	✓	✓
	2.222.02.00007			-	✓	-	-
<b>Direct Connection Lead with large clips</b>							
	2.213.02.00013	Direct Connection Lead with large clips is suited for the gas and water industries where connections will be made to bell housings or fire hydrants.		✓	-	✓	✓
	2.219.02.00090			-	✓	-	-
<b>Direct Connection Lead with Telco Clip</b>							
	2.213.02.00007	Direct Connection Lead with Telco clips is suitable for telephone cable where the user cannot access the sheath of the cable.		✓	-	✓	✓
	2.219.02.00091			-	✓	-	-
<b>Ground Extension Lead</b>							
	2.200.04.00082	Ground Extensions - Use the extension leads to extend the ground connection to reach a suitable grounding position.	30 feet	✓	✓	✓	✓
	2.200.04.00081		98 feet	✓	✓	✓	✓
<b>Clamp and Leads Adapter</b>							
	2.219.02.00094	Adapter, 3 pin silver plug to Twist/Lock plug.	-	✓	-	✓	✓
<b>Live Cable Connector</b>							
	1.204.10.00001	Live Cable Connector is usable on live cables up to 480 V ac 60/50Hz. The Live Cable Connector operates on frequencies of 8kHz, 33kHz and SIS.		✓	-	✓	✓
	1.204.10.00002			-	✓	-	-
<b>Live Plug Connector</b>							
	1.204.07.00002	Live Plug Connector is used to safely inject a locate frequency onto a live street distribution cable using a standard household mains socket from a building.		✓	-	✓	✓
	1.204.07.00005			-	✓	-	-




## Transmitter Clamps

Picture	Order Code	Description	Plug Type	5-Watt 10-Watt SiS	25-Watt	VM-550FF VM-560FF vScan	VM-810	VM-850
	1.200.03.00011	2" / 50mm Signal Clamp		✓	-	✓	✓	✓
	1.200.15.00001			-	✓	-	-	-
	1.200.03.00012	4" / 100mm Signal Clamp		✓*	-	✓	✓	✓
	1.222.03.00001			✓*	✓	-	-	-
	1.200.03.00004	5" / 125mm Signal Clamp		✓*	-	✓	✓	✓
	1.222.04.00001			✓*	✓	-	-	-
	1.219.09.00001	5" / 125mm SiS Signal Clamp		✓	✓	-	-	-
	1.219.08.00002	9" / 230mm Signal Clamp		✓*	-	✓	✓	✓
	1.219.08.00001			✓*	✓	-	-	-
	1.200.03.00006	18" / 450mm Flexible Signal Clamp		✓	-	✓	✓	-

### Clamp and Leads Adapter

	2.219.02.00094	Adapter, 3 pin silver plug to Twist/Lock plug.		✓	-	✓	✓	✓
---	----------------	---	--	---	---	---	---	---

### Clamp extension rod

	1.204.08.00001	The extension rod is compatible with all clamps except the 18" flexible.
---	----------------	--

 3 Pin Silver Plug

 Twist/Lock plug

\* SiS 8.44kHz and 9.82kHz

Local Vivax-Metrotech Distributor:

### Vivax-Metrotech Corporation

3251 Olcott Street, Santa Clara, CA 95054, USA

**T/Free: 1-800-446-3392**

**Tel: +1-408-734-3880**

www.vivax-metrotech.com

Tag us on social media @vivax\_metrotech



V1.0

Please visit our website for full product specifications.