



VIVAX
METROTECH

Live Transmitter Connectors

Technical Specifications V1.0



Live Cable Connector (LCC)



Live Plug Connector (LPC)

Worldwide Locations

World Headquarters, United States of America

Vivax-Metrotech Corporation
3251 Olcott Street, Santa Clara, CA 95054, USA

T/Free : 1-800-446-3392
Tel : +1-408-734-3880
Website: www.vivax-metrotech.com
Email : SalesUSA@vxmt.com

Central/South America and the Caribbean

Ventas para América Latina
3251 Olcott Street, Santa Clara, CA 95054, USA

T/Free : 1-800-446-3392
Tel : +1-408-734-3880
Website: www.vivax-metrotech.com
Email : LatinSales@vxmt.com

Canada

Vivax Canada, Inc.
41 Courtland Ave Unit 8, Vaughan, ON L4K 3T3, Canada

Tel : +1-289-846-3010
Fax : +1-905-752-0214
Website: www.vivax-metrotech.ca
Email : SalesCA@vxmt.com

United Kingdom

Vivax-Metrotech Ltd.
Unit 1, B/C Polden Business Centre, Bristol Road, Bridgwater, Somerset, TA6 4AW, UK

Tel : +44(0)1793 822679
Website: www.vivax-metrotech.co.uk
Email : SalesUK@vxmt.com

France

Vivax-Metrotech SAS
Technoparc - 1 allée du Moulin Berger, 69130 Ecully, France

Tel : +33(0)4 72 53 03 03
Fax : +33(0)4 72 53 03 13
Website: www.vivax-metrotech.fr
Email : SalesFR@vxmt.com

Germany

Metrotech Vertriebs GmbH
Am steinernen Kreuz 10a
96110 Schesslitz


Tel : +49 9542 77227-43
Website: www.vivax-metrotech.de
Email : SalesEU@vxmt.com

China


Vivax-Metrotech (Shanghai) Ltd.
Building 10, Lane 1158 Zhongxin Rd.,
Songjiang District, Shanghai, China, 201615

Tel : +86-21-5109-9980
Website: www.vivax-metrotech.com
Email : SalesCN@vxmt.com.cn

A. Live Cable Connector Typical Applications

Item	Parameter
Model name and number	Live Cable Connector (LCC) VX204-10
Intended Use	Live Cable Connector: The Live Cable Connector applies a locate signal on live cables up to 480V AC 60/50Hz.
Warning 	The live Cable Connector (LCC) should only be used by approved operatives who adhere to company regulations and work practices and wear appropriate safety equipment and clothing.


Live Cable Connector



The **Live Cable Connector** is usable on live cables up to 480 V AC 60/50Hz. It operates on frequencies of 8kHz, 33kHz, and SIS. The Transmitter provides power; the output leads from the separation filter can be connected to conductors carrying up to 480V AC.

B. Live Cable Connector Characteristics


Item	Parameter
Construction	Polycarbonate plastic
Weight	1.5lbs (0.7kg)
Dimension	6.3in(L) x 3.1in(W) x 2.2in(H) (160mm x 80mm x 56mm)
Temperature Range	<ul style="list-style-type: none"> - Operating: -4°F to 122°F (-20°C to 50°C) - Storage: -40°F to 140°F (-40°C to 60°C)
Power Supply	Provided by the transmitter
External Connectors	Red and black test clips/banana plug lead connects to the live cable or a banana socket. Female speakON® plug (blue) or 3-pin XLR plug (silver)
Controls	None
Frequency Range	8.192kHz, 32.768kHz, 8.44kHz SIS
Manufacturing	Designed and manufactured per ISO 9001:2015
Compliance/Approvals	<ul style="list-style-type: none"> - Complies with European standard CE (Directive 2004/108/EC) <ul style="list-style-type: none"> • EN 61326-1 - EN 61010-1 EN 61010-2 - Complies with FCC Rules Part 15 <ul style="list-style-type: none"> • CAT III • UL94 HB

What's in the Box	<ul style="list-style-type: none"> - Live Cable Connector - Quick Guide
Compatible Transmitters	5, 10 and 25-Watt Loc and Loc3 series transmitters, VM series transmitters and vScan transmitters.
Warning 	The live Cable Connector should only be used by approved operatives adhering to company regulations and work practices while using appropriate safety equipment and clothing.

C. Live Plug Connector Typical Applications

Item	Parameter
Model name and number	Live Plug Connector (LPC Separation Filter) VX204-7
Intended Use	Live Plug Connector: The Live Plug Connector (LPC separation filter) safely injects a location frequency onto a live street distribution cable using a standard household mains socket from a building.

Live Plug Connector



The **Live Plug Connector** can locate frequency onto a live street distribution cable using a standard household mains socket from a building. This allows the cable to be traced to the street connection from the premises. The Live Plug Connector connects voltages between 100V AC and 250V AC.

D. Live Plug Connector Characteristics

Item	Parameter
Construction	High-impact ABS injection molded housing
Weight	0.8lbs (0.36kg)
Dimension	2.5-inch (Dia.) x 6.2-inch (L) (64mm x 156.4mm)
Temperature Range	<ul style="list-style-type: none"> - Operating: -4°F to 122°F (-20°C to 50°C) - Storage: -40°F to 140°F (-40°C to 60°C)
Power Supply	Power is supplied from the connected transmitter.
External Connectors	1 x speakON® plug (blue) or 3-pin XLR plug (silver) 1 x 3-Pin AC Plug (per region) for up to 240V AC

Controls	Rotary knob – phase switching
Frequency Range	8 kHz, 33 kHz, 65 kHz
Manufacturing	Designed and manufactured per ISO 9001:2015
What's in the Box	<ul style="list-style-type: none"> - Live Plug Connector - 3-Pin Power cord (per region) - Quick Guide
Compatible Transmitters	5, 10 and 25-Watt Loc and Loc3 series transmitters, VM series transmitters and vScan transmitters.

E. Shipping

Item	Parameter
Shipping Weight	Live Cable Connector: 2.1lbs (0.94kg) Live Plug Connector: 1.4lbs (0.64kg)
Shipping Dimension	Live Cable Connector: 10in(L) x 9.3in(L) x 3.3in(L) (253mm x 237mm x 84mm) Live Plug Connector: 8.7-inch(L) x 5-inch(W) x 2.7-inch(H) (222mm x 127mm x 68mm)

F. Warranty

Item	Parameter
Warranty	12 months

Disclaimer: Product and accessory specification and availability information are subject to change without prior notice.